

# Material Safety Data Sheet

## 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND COMPANY

**Product Description** E Glass Rope Lagging

<u>Product Category</u>	<b>E Glass Rope Lagging</b>
-------------------------	-----------------------------

<b>Supplier</b>	Cheshire Ribbon Manufacturing Kingston Mills Manchester Road Hyde Cheshire	Date of Issue: March 2009 Prepared by: E Ashworth
	Tel No. for information / emergency	0161 368 2048
	Fax No. " " "	0161 367 8193

## 2. COMPOSITION / INFORMATION ON INGREDIENTS

The product covered by this data sheet is based on continuous filament fibres made from borosilicate E Glass (CAS-65997-17-3). The filament diameters are uniform and are therefore above the maximum size considered to be respirable (approx. 3 micron). They will not sub-divide into fibrils of a smaller diameter. The fibres contain small amounts of complex organic surface dressings (e.g. starch based and PVA compounds). This product also contains a small amount of polypropylene filament (max. 1%).

## 3. HAZARD INFORMATION

These products are classified as low hazard.

#### **4. FIRST AID MEASURES**

**Inhalation**

In the unlikely event of excessive inhalation of dust, (or fumes from a sustained fire situation), remove the individual to the fresh air. Obtain medical advice.

**Skin Irritation**

In the unlikely event of skin irritation wash affected part with mild soap and water. If irritation persists obtain medical advice.

**Eye Irritation**

Irrigate eyes if affected by entry of dust. Obtain medical advice if irritation persists.

## 5. FIRE-FIGHTING MEASURES

<b>Flammability</b>	The materials will not support combustion.
<b>Special Firefighting Procedures</b>	In a sustained fire the products will degrade. The surface dressings will give rise to fumes and smoke. Appropriate forms of self-contained breathing apparatus should therefore be worn in such situations.
<b>Extinguishing Media</b>	Use that appropriate to the surrounding fire.

## 6. ACCIDENTAL RELEASE MEASURES

Fabric that is fire damaged or made friable should be handled with the use of personal protective equipment.

## 7. HANDLING AND STORAGE

It is highly unlikely that these fabrics will give rise to significant amounts of dust during normal handling and dust control measures will rarely be required in circumstances involving the fabrication of products from them. However, in accordance with good working practices, the production of debris should be minimised and the accumulation of dust should be removed by dust-less methods. No special storage conditions are required on health grounds.

## 8. EXPOSURE CONTROL / PERSONAL PROTECTION

Workplace exposure to mineral fibre dust of non-respirable size should be kept to the minimum that is reasonably practicable and should not exceed a Workplace Exposure Limit of 5mg/m<sup>3</sup> (8 hour TWA) (Ref. 1).

Dust levels are only likely to arise above the exposure limit if the materials are handled extremely vigorously or subjected to harsh mechanical abrasion. In such circumstances, the provision of local exhaust ventilation should be considered. Should this not be practicable, protective masks approved for use against irritant dust should be worn in accordance with their manufacturer's instructions.

To reduce the chance of skin irritation during the handling of glass fibre based materials, protective overalls of a closely woven structure should be worn. Gloves, arm cuffs or barrier creams may also be advantageous in some circumstances. Emphasis should, however, be placed on personal hygiene, ensuring that hands and arms are washed with copious quantities of cool running water to remove any loose fibres before application of soap for washing purposes.

Where there is a possibility of glass fibre entering the eye, suitable eye protection should be worn.

## 9. PHYSICAL AND CHEMICAL PROPERTIES.

<b>Weights</b>	See appropriate Product Data Sheets
<b>Appearance</b>	The products are white.
<b>Odour</b>	The products have no discernible odour.
<b>Solubility in Water</b>	Insoluble
<b>Melting Point</b>	> 700 °C
<b>Boiling Point</b>	Not applicable
<b>Vapour Pressure</b>	Not applicable
<b>Percent Volatile (vol.)</b>	Not applicable
<b>Evaporation rate</b>	Not applicable

## 10. STABILITY AND REACTIVITY

The products are stable under normal conditions of use.

## 11. TOXICOLOGICAL INFORMATION

### Primary Routes of Potential Exposure

Inhalation, skin and eye contact.

### Effects of Over-exposure (Acute and Chronic)

<b>Inhalation (Dust)</b>	In view of the diameter of the continuous glass filaments used for the construction of this product, dust derived from the materials referred to is not generally considered to be respirable. For the majority of operations associated with the handling and use of these materials, the quantity of dust generated is expected to be negligible. Products subjected to harsh mechanical abrasion may give rise to dust that could be irritating to the upper respiratory tract. Such effects are usually transitory leaving no permanent damage. Contact with molten metal or flame may give rise to localised emission of fume.
<b>Skin Irritation</b>	Some people who come into contact with glass fibre experience reddening and itching of the skin. Those who are subject to this effect are most likely to experience it when handling the materials for the first time or after a period of no contact as hardening of the skin usually occurs. People with a history of skin complaints may be particularly susceptible and, in general, should not come into contact with glass fibre.
<b>Eye Irritation</b>	Entry of glass fibre into the eye will cause foreign body irritation.
<b>Carcinogenicity</b>	Continuous glass filament is not classified as a carcinogen.

## 12. ECOLOGICAL INFORMATION

This product is not associated with any known ecological problems.

## 13. DISPOSAL CONSIDERATIONS

The disposal of waste should be carried out in accordance with national or regional directives - normally by burial in controlled industrial landfill sites.

## 14. TRANSPORT INFORMATION

All products are labelled as in [Section 2](#) and transported double-wrapped to prevent damage and water ingress.

## 15. REGULATORY INFORMATION

No specific regulatory information is applicable to these glass textiles.

## 16. OTHER INFORMATION

### References

1, Health & Safety Executive Guidance Note EH 40/2005 Workplace Exposure Limits 2005

For further information contact:

CHESHIRE RIBBON MANUFACTURING

### NOTE:

This Data Sheet relates to the material as supplied. The information contained herein is given in good faith, but no liability will be accepted by the Company in relation to same. The acquisition of additional information may necessitate revisions to parts or all of this Data Sheet, and such information will be supplied as it becomes available.

As the Company's products are used for a multiplicity of purposes, and as the Company has no control over the method of their application or use, the Company excludes all conditions or warranties, express or implied, by statute or otherwise, as to their products and/or their fitness for any particular purpose.

Any technical co-operation between the Company and the Customer is given for the Customer's assistance only and without liability on the part of the Company.